

In The Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (currently amended) A thermoelectric device comprising:
at least one unipolar couple element having ~~two~~ first and second legs of a same electrical conductivity type;
a first-temperature stage connected to ~~one~~ the first leg of said two legs;
a second-temperature stage connected across ~~said~~ the first and second legs of the at least one unipolar couple element; and
a third-temperature stage connected to the ~~other~~ second leg of said two legs, wherein the first leg is between the first-temperature stage and the second-temperature stage, and wherein the second leg is between the second-temperature stage and the third temperature stage.
2. (currently amended) The device of claim 1, wherein said at least one unipolar couple element is configured such that currents flow in opposite directions in the ~~two~~ first and second legs of the same electrical conductivity type of the at least one unipolar couple element to establish a temperature differential across each of the ~~two~~ first and second legs of said unipolar couple element.
3. (withdrawn and currently amended) The device of claim 1, wherein said at least one unipolar couple element is configured to generate at least one of an electrical potential and an electrical current from a temperature differential established across the ~~two~~ first and second legs of said unipolar couple element.
4. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element ~~comprises~~ comprise respective first and second a

~~pair of~~ p-type $\text{Bi}_2\text{Te}_3/\text{Sb}_2\text{Te}_3$ superlattice thermoelements.

5. (currently amended) The device of claim 4, wherein the first and second p-type $\text{Bi}_2\text{Te}_3/\text{Sb}_2\text{Te}_3$ superlattice thermoelements have a ZT of >1 at 300K.

6. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element ~~comprises:~~ comprise respective first and second a ~~pair of~~ n-type $\text{Bi}_2\text{Te}_3/\text{Bi}_2\text{Te}_{3-x}\text{Se}_x$ superlattice thermoelements.

7. (original) The device of claim 8, wherein the n-type $\text{Bi}_2\text{Te}_3/\text{Bi}_2\text{Te}_{3-x}\text{Se}_x$ superlattice thermoelements have a ZT >1 at 300K.

8. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element ~~comprises:~~ comprise respective first and second a ~~pair of~~ n-type $\text{PbTeSe}/\text{PbTe}$ superlattice thermoelements.

9. (currently amended) The device of claim 8, wherein the first and second n-type $\text{PbTeSe}/\text{PbTe}$ elements ~~comprise:~~ comprise respective first and second a ~~pair of~~ n-type $\text{PbTeSe}/\text{PbTe}$ quantum-dot superlattice thermoelements having a ZT of ~ 1.6 at 300K.

10. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element ~~comprises:~~ comprise respective first and second a ~~pair of~~ p-type $\text{PbTeSe}/\text{PbTe}$ superlattice thermoelements.

11. (currently amended) The device of claim 1, wherein the at least one unipolar couple element ~~comprises:~~ comprises a first unipolar couple element having the first and second legs comprising respective first and second p-type thermoelements, and wherein the at least one unipolar couple element comprises a second unipolar couple element having first and second n-type thermoelements ~~at least one set of p-p and one set of n-n unipolar couple~~

elements.

12. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element comprises: comprise respective first and second p-type thermoelements, and wherein the at least one unipolar couple element further comprises one set of p-p couples and two independent legs of n.

13. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element comprises: comprise respective first and second n-type thermoelements, and wherein the at least one unipolar couple element further comprises one set of n-n couples and two independent legs of p.

14. (currently amended) The device of claim 1, wherein the first and second legs of the unipolar couple elements comprise a p-p bulk couple respective first and second p-type bulk thermoelements.

15. (currently amended) The device of claim 1, wherein the first and second legs of the unipolar couple elements comprise a n-n bulk couple respective first and second n-type bulk thermoelements.

16. (currently amended) The device of claim 1, wherein the at least one unipolar couple element is elements are configured to produce temperature differentials in a range from 1K to 200K.

17. (original) The device of claim 1, further comprising:
a thermal insulation between said first-temperature stage and said third-temperature stage wherein the first and second legs of the same electrical conductivity type and the first-temperature stage and the third-temperature stage are on a same side of the second-temperature stage.

18. (original) The device of claim 17, wherein the thermal insulation comprises at least one of aerogels and polymer sheets.

19. (original) The device of claim 1, further comprising:
a controller configured to control a temperature of the second-temperature stage to produce desired source and drain temperatures on the first-temperature stage and the third-temperature stage, respectively.

20. (original) The device of claim 19, wherein said controller is configured to control said current flow to produce said desired source and drain temperatures.

21. (currently amended) The device of ~~claim 1~~ claim 2, wherein said temperature differential across each of the first and second ~~leg of said two~~ legs is about half a temperature differential between the first-temperature stage and the second-temperature stage.

22. (currently amended) The device of claim 1, wherein at least one of the first-temperature stage and the second-temperature stage comprises a split ~~header~~ stage.

23. (original) The device of claim 1, wherein said third-temperature stage is configured to operate at a temperature about 100 C so that a phase change of water to steam provides heat removal and said first-temperature stage is configured to operate at a temperature below 40 C.

24. (currently amended) The device of claim 1, wherein said third-temperature stage is configured to operate at a temperature about ~~100 C~~ 100 C so that a phase change of water to steam provides heat removal and said first-temperature stage is configured to operate at a temperature below 10 C or below.

25. (original) The device of claim 1, further comprising:
a water-based closed cycle heat removal system connected to the third-temperature stage.

26. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element comprises: comprise respective first and second p-type thermoelements ~~a p-p couple~~ with ~~each~~ the first and second p-type thermoelements leg of said two legs having at least one of ~~a different~~ different material ~~composition~~ compositions and ~~a different~~ different ~~structures~~ structure ~~from the other leg~~.

27. (currently amended) The device of claim 26, wherein the ~~p-p couple~~ comprises: first and second p-type thermoelements respectively comprise a p-type $\text{Bi}_{1.0}\text{Sb}_{1.0}\text{Te}_3$ thermoelement; thermoelement and a p-type $\text{Bi}_{0.5}\text{Sb}_{1.5}\text{Te}_3$ thermoelement.

28. (currently amended) The device of claim 26, wherein the p-p couple comprises: first and second p-type thermoelements respectively comprise a p-type 10 Angstrom/30 Angstrom $\text{Bi}_2\text{Te}_3/\text{Sb}_2\text{Te}_3$ superlattice thermoelement; thermoelement and a p-type 10 Angstrom/50 Angstrom $\text{Bi}_2\text{Te}_3/\text{Sb}_2\text{Te}_3$ superlattice thermoelement.

29. (currently amended) The device of claim 1, wherein the first and second legs of the at least one unipolar couple element comprises: comprises respective first and second n-type thermoelements ~~a n-n couple~~ with ~~each leg of said two legs~~ the first and second n-type thermoelements having at least one of ~~a different~~ different material ~~composition~~ compositions and ~~a different~~ different ~~structures~~ structure ~~from the other leg~~.

30. (currently amended) The device of claim 29, wherein the ~~n-n couple~~ comprises: the first and second n-type thermoelements respectively comprise an n-type $\text{Bi}_2\text{Te}_{2.5}\text{Se}_{0.5}$ thermoelement; thermoelement and an n-type $\text{Bi}_2\text{Te}_{2.85}\text{Se}_{0.15}$ thermoelement.

31. (currently amended) The device of claim 29, wherein the ~~n-n couple comprises:~~
the first and second n-type thermoelements respectively comprise an n-type 10 Angstrom/30
Angstrom Bi₂Te₃/Bi₂Te_{2.85}Se_{0.15} superlattice thermoelement; thermoelement and an n-type 10
Angstrom/50 Angstrom Bi₂Te₃/Bi₂Te_{2.85}Se_{0.15} superlattice thermoelement.

32. – 55. (canceled)

56. (new) The device of claim 1, wherein the at least one unipolar couple element is configured such that currents flow in opposite directions in the two legs of the same electrical conductivity type of the at least one unipolar couple element.

57. (new) The device of claim 56, wherein the first and second legs of the same electrical conductivity type and the first-temperature stage and the third-temperature stage are on a same side of the second-temperature stage, and wherein the first-temperature stage and the third temperature stage are spaced apart.

58. (new) The device of claim 56, wherein the first and second legs of the same conductivity type comprise respective first and second materials wherein the first and second materials are different.

59. (new) The device of claim 56 wherein the first and second legs of the same conductivity type have respective first and second structures wherein the first and second structures are different.

60. (new) The device of claim 56 wherein the first and second legs of the same conductivity type comprise respective first and second superlattice thermoelements having respective first and second superlattice periods wherein the first and second superlattice periods are different.

61. (new) The device of Claim 56 wherein the first leg comprises a p-type $\text{Bi}_{1.0}\text{Sb}_{1.0}\text{Te}_3$ thermoelement, and wherein the second leg comprises a p-type $\text{Bi}_{0.5}\text{Sb}_{1.5}\text{Te}_3$ thermoelement.

62. (new) The device of Claim 56 wherein the first-temperature stage and the second-temperature stage are spaced apart, wherein the second-temperature stage and the third-temperature stage are spaced apart, and wherein the first-temperature stage and the third-temperature stage are spaced apart.